



Polyethylene food hose and pharmaceutical hose, medium-heavy

Applications

- flexible hose/ ducting for gases and for dust, powder, fibres
- food industry, pharmaceutical industry: food-stuff, pharmaceutical
- conveying of dry foods e.g. rice, cereals, sugar, milk powder, powders, coffee, tea, grains, flour, frozen foods
- mixer, dryer, packaging machine, bulk-bag (big bag)-charging and discharging, mill
- tobacco industry: cigarette machine, tobacco conveying
- galvanic extraction
- chemical industry: chemical vapours, vapour return hose at loading arm, paint steam, spray mist extraction

Properties

- medium-heavy duty
- Food grade wall, complies with: FDA 21 CFR 177.1520 3.1 and 3.2, EU-Directive 10/2011 and EC 1935/2004
- odourless and tasteless
- good resistance to alkalis and acids
- extremely good resistance to chemicals
- manufacturing process acc. GMP EC 2023/2006
- conforms to RoHS guideline

Temperature Range

- 35°C to 80°C

Design, Material

AIRDUC® profile hose

- spring steel wire firmly embedded in wall
- wall: special polyethylene (PE)
- wall thickness 0,8 mm approx.

Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- special colours: full coloured
- customer-specific branding

I.D. in / mm	O.D. mm	Over- pressure bar	Under- pressure bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Order No.
1 / 25	30	1,455	0,570	17	0,210	10 15	362-0025-0000
- / 28	34	1,375	0,540	20	0,250	10	362-0028-0000
- / 30	37	0,980	0,520	22	0,210	10	362-0030-0000
1,25 / 32	39	0,920	0,505	23	0,230	10	362-0032-0000
1,5 / 38	45	0,780	0,475	26	0,260	10	362-0038-0000
- / 40	47	0,740	0,460	27	0,280	10	362-0040-0000
1,75 / 44-45	52	0,660	0,430	30	0,310	10	362-0045-0000
2 / 50-51	57	0,595	0,395	32	0,340	10	362-0050-0000
- / 55	62	0,540	0,350	35	0,370	10	362-0055-0000
2,36 / 60	67	0,500	0,320	37	0,400	10	362-0060-0000
2,5 / 63-65	72	0,460	0,275	40	0,440	10	362-0065-0000
- / 70	79	0,430	0,230	44	0,560	10	362-0070-0000
3 / 75-76	84	0,400	0,210	47	0,600	10	362-0075-0000
- / 80	89	0,375	0,200	49	0,640	10	362-0080-0000
3,5 / 89-90	99	0,335	0,170	54	0,710	10	362-0090-0000
4 / 100-102	109	0,300	0,135	59	0,790	10	362-0100-0000
- / 110	119	0,275	0,120	64	0,860	10	362-0110-0000
4,72 / 120	129	0,250	0,115	69	0,940	10	362-0120-0000
5 / 125-127	134	0,240	0,090	72	0,980	10	362-0125-0000
6 / 150-152	159	0,200	0,090	84	1,160	10	362-0150-0000
6,3 / 160	169	0,190	0,075	89	1,240	10	362-0160-0000
8 / 200-203	210	0,150	0,060	110	1,550	10	362-0200-0000
- / 250	260	0,120	0,025	135	1,920	10	362-0250-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional technical data at www.norres.com/en/technology/

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at www.norres.com. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.

Accessories



CLAMP 212



CLAMP 210 BRIDGE CLAMP



CLAMP 212 EC



CLAMP 217



CLAMP 213



CONNECT 228



CONNECT 223



CONNECT 270-271

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at www.norres.com. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.