

## SAFE-WRAP

SAFE-WRAP is produced from 100 % polyamide with PU coating and Velcro®-brand fasteners which make it very easy and fast to install on hose assemblies afterwards and repeatedly. This makes Safe-Wrap a very cost-effective solution for hose protection and hose bundling. It can be equipped with mounting eyelets and / or straps, too.

Safe-Wraps tensile strength is excellent (EN ISO 13934-1) and water repellence of the fabric is 100 % (EN 24920).

The operating temperature is between -20 °C to +120 °C.

Safe-Wrap also fulfils the demands of standard ISO 3457 (pin hole –approved).

This product is very abrasion resistant.



### Safeplast article no. for standard sizes

	in 25 m rolls		in 10 m rolls:
40 mm	WR-RD40R25	/	WR-RD40R10
60 mm	WR-RD60R25	/	WR-RD60R10
80 mm	WR-RD80R25	/	WR-RD80R10
100 mm	WR-RD100R25	/	WR-RD100R10
120 mm	WR-RD120R25	/	WR-RD120R10



Other diameters (Ø 20 mm to 400 mm, in 5 mm intervals) are offered on request.

Standard roll lengths: 10 m and 25 m  
Other roll lengths up to 50 m and fixed lengths are produced after order.

