




GUIDACATENE IN POLIETILENE CHAIN GUIDE RAILS IN POLYETHYLENE


PROFILO "CT" PER CATENA DOPPIA

| tipo | catena | codice | ISO | B | A | a | b | Ac | Kg./Mt. |
|---------------|--------------|------------|------|------|----|-----|------|----|---------|
| T 0.2 C3 A 15 | 3/8" x 7/32" | 6011123301 | 06B2 | 15,7 | 15 | 1,5 | 5,4 | 17 | 0,66 |
| T 1.2 C3 A 15 | 1/2" x 5/16" | 6011123401 | 08B2 | 21,4 | 15 | 2,2 | 7,4 | 17 | 0,70 |
| T 2.2 C5 A 15 | 5/8" x 3/8" | 6011123501 | 10B2 | 25,9 | 15 | 2,6 | 9,2 | 19 | 0,95 |
| T 3.2 C5 A 15 | 3/4" x 7/16" | 6011123601 | 12B2 | 30,7 | 15 | 2,4 | 11,3 | 19 | 0,97 |
| T 4.2 C9 A 20 | 1" x 17,02 | 6011123801 | 16B2 | 48,3 | 20 | 3,5 | 16,5 | 27 | 1,61 |




PROFILO "C 10 P" PER CATENA SEMPLICE

| tipo | catena | codice | ISO | B | A | b | a | Kg./Mt. |
|--------|--------------|------------|------|----|----|------|------|---------|
| C 10.0 | 3/8" x 7/32" | 6011143301 | 06B1 | 30 | 24 | 6,6 | 5,6 | 1,39 |
| C 10.1 | 1/2" x 5/16" | 6011143401 | 08B1 | 30 | 24 | 8,7 | 7,6 | 1,33 |
| C 10.2 | 5/8" x 3/8" | 6011143501 | 10B1 | 30 | 24 | 10,4 | 9,5 | 1,29 |
| C 10.3 | 3/4" x 7/16" | 6011143601 | 12B1 | 30 | 24 | 12,3 | 11,5 | 1,23 |
| C 11.4 | 1" x 17,02 | 6011143801 | 16B1 | 45 | 40 | 16,1 | 16,9 | 2,92 |




PROFILO "COMBI A-R" PER CATENA SEMPLICE

| tipo | catena | codice | ISO | Prof. met. | A | B | A1 | A2 | Ac | b | Kg./Mt. |
|---------|--------------|------------|------|------------|------|----|------|------|------|------|---------|
| COMBI 0 | 3/8" x 7/32" | 6011153301 | 06B1 | C 3 | 26,4 | 20 | 31,6 | 19,5 | 28,4 | 17,3 | 0,84 |
| COMBI 1 | 1/2" x 5/16" | 6011153401 | 08B1 | C 3 | 28,0 | 20 | 34,8 | 18,9 | 30,5 | 16,5 | 0,81 |
| COMBI 2 | 5/8" x 3/8" | 6011153501 | 10B1 | C 3 | 34,4 | 20 | 41,1 | 21,2 | 36,0 | 15,5 | 0,87 |
| COMBI 3 | 3/4" x 7/16" | 6011153601 | 12B1 | C 5 | 38,5 | 28 | 47,5 | 24,8 | 41,5 | 22,3 | 1,36 |
| COMBI 4 | 1" x 17,02 | 6011153801 | 16B1 | C 9 | 52,4 | 38 | 69,4 | 34,0 | 61,4 | 29,7 | 2,25 |




PROFILI METALLICI - ZINCATI

| tipo | codice | A | B | C | S | Kg./Mt. |
|------|------------|----|----|----|-----|---------|
| C3 | 6011180003 | 10 | 20 | 10 | 1,5 | 0,46 |
| C5 | 6011180005 | 12 | 28 | 14 | 1,5 | 0,64 |
| C9 | 6011180009 | 18 | 38 | 22 | 1,5 | 0,93 |
| C10 | 6011180010 | 24 | 30 | 20 | 1,5 | 0,89 |
| C11 | 6011180011 | 40 | 45 | 31 | 2 | 1,96 |



PROFILI METALLICI - INOX

| tipo | codice | A | B | C | S | Kg./Mt. |
|------|------------|----|----|----|-----|---------|
| C3 | 6011190003 | 10 | 20 | 10 | 1,5 | 0,46 |
| C5 | 6011190005 | 12 | 28 | 14 | 1,5 | 0,64 |
| C9 | 6011190009 | 18 | 38 | 22 | 1,5 | 0,93 |
| C10 | 6011190010 | 24 | 30 | 20 | 1,5 | 0,89 |



CARATTERISTICHE TECNICHE POLIETILENE

MATERIALE : PE UHMW Polietilene ad altissima densità.

PESO SPECIFICO : 0,94 gr/cm³

DUREZZA : Shore D 64/67

TEMPERATURA D'IMPIEGO : Fino a 80° C

COEFFICIENTE : mm/° c 2 x 10⁻⁴

DI DILATAZIONE TERMICA : (2 mm/mt per ogni 10° C)