



Kratzerketten nach DIN 8165 und DIN 8167

Scraper conveyor chains according to DIN 8165 and DIN 8167

iwis.de/80118

Kettentyp	Teilung					Lichte Weite	Bolzen Ø	Buchsen Ø	Laschen- höhe	Laschen- dicke	Abstand Mitte Bolzen bis Kratzer	Kratzerlänge	min. Bruchkraft
Chain no.	Pitch					Width between inner plates	Pin Ø	Bush Ø	Plate height	Plate thickness	Pin to top of scraper	Length of scraper	Min. tensile strength
	p					b1 min.	d2 max.	d3 max.	h2	T/t	h4	W	F min.
	mm					mm	mm	mm	mm	mm	mm	mm	KN
MR Serie / DIN 8167													
MR 56	100	125				24	10	15	30	4,00	20		56,0
MR 80	100	125	160			28	12	18	35	5,00	25		80,0
MR 112	100	125	160			32	15	21	40	6,00	35		112,0
MR 160	100	125	160			37	18	25	50	7,00	40		160,0
MR 224		125	160	200		43	21	30	60	8,00	44		224,0
MR 315			160	200	250	48	25	36	70	10,00	50		315,0
FVR Serie / DIN 8165													
FVR 40	80	100	125			18	10	15	25	3,00	20		40,0
FVR 63		100	125	160		22	12	18	30	4,00	25		63,0
FVR 90		100	125	160		25	14	20	35	5,00	30		90,0
FVR 112		100	125	160		30	16	22	40	6,00	35		112,0
FVR 140			125	160	200	35	18	26	45	6,00	38		140,0
FVR 180			125	160	200	45	20	30	50	8,00	44		180,0
FVR 250				160	200	55	26	36	60	8,00	50		250,0

Abmessung muss bei Bestellung mit angegeben werden
Please specify dimension with the order

