

# TWT

TIPO TYPE	Ø INTERNO INSIDE Ø	SPESSORI PARETE / WALL TH	PESI / WEIGHTS	ESERCIZIO (20°C) SERVICE (68°F)	SCOPPIO (20°C) BURST (68°F)
	(mm)	(mm)	(gr/mt)	(bar)	(bar)
TWT	1	0,5	6	42	127
TWT	1	1	15	63	190
TWT	2	0,5	9	25	76
TWT	2	1	22	42	127
TWT	3	1	29	32	95
TWT	3	1,5	49	42	127
TWT	4	1	37	25	76
TWT	4	1,5	60	35	104
TWT	5	1	44	21	63
TWT	5	1,5	71	29	88
TWT	6	1	51	18	54
TWT	6	1,5	82	25	76
TWT	6,5	1	55	17	51
TWT	7	1	58	16	48
TWT	7	1,5	93	22	67
TWT	8	1	66	14	42
TWT	8,5	1	69	13	40
TWT	9	1	73	13	38
TWT	10	1	80	12	35
TWT	10,5	1	84	11	33
TWT	11	1	87	11	32
TWT	12	1	95	10	29
TWT	12,5	1	98	9	28
TWT	13	1	102	9	27
TWT	14	1	109	8	25
TWT	15	1	116	7	21
TWT	16	1	123	7	21
TWT	18	1	137	5	16
TWT	20	1	152	5	16
TWT	22	1	167	4	12
TWT	23	1	175	3,8	11,7
TWT	24	1	182	3,7	11,2
TWT	25	1	189	3,5	10,7
TWT	30	1	225	3	9
TWT	31	1,5	353	4,3	13
TWT	32	1	240	2,8	8
TWT	36	1	269	2,5	7,5
TWT	38	1	282	2,3	7,1
TWT	41,5	1	308	2,1	6,5
TWT	42	1	312	2,1	6,5
TWT	50	1	370	1,8	5,5

Tolleranza / Tolerance UNI EN ISO 13000 - 1:2005